

VRX1000 VEHICLE RADIO EXTENDER



Public safety agencies and utilities seeking alternative methods for portable radio coverage enhancement can safely rely on the VRX1000 Vehicle Radio Extender.

The VRX1000 is a compact 3W simplex radio extender integrated with Motorola APX™ 4500, APX™ 6500 and APX™ 7500 series mobile radios. A scaled down version of the industry leading 10W full duplex DVRS, the VRX1000 improves portable radio coverage while keeping users connected to either conventional or trunked networks. The small size of VRX1000 allows it to be easily installed in patrol cars and utility trucks.

Key Features & Benefits

- Programmable output power: 0.5 – 3 watts
- Simplex operation.
- Analog operation with P25 software upgrades available.
- Available in VHF, UHF, 700/800 MHz bands.
- Integrates with remote mount APX™4500, APX™6500 and APX™7500 mobile radios.
- In-Band or Cross-Band configurations.
- Operated through mobile radio control head.
- Sold exclusively through Motorola Solutions.

General Specifications

Dimensions: Height / Width / Depth:

45 mm (1.7") x 175 mm (6.8") x 160 mm (6.2")
(cross band, no filters)

Weight:

2kg / 4.4 lbs (cross band, no filters)

Channel Spacing:

12.5 or 25 kHz programmable

Number of Channels:

192 (1 Channel when in VRS750 compatible mode)

Number of VRX Enabled Mobile Radio Channels:

2047 entries

CTCSS/DCS:

Programmable per Analog Channel

Power Supply:

13.8V DC +/- 20%, negative ground only

Equipment Type Acceptance

FCC
Industry Canada

VHF	UHF	700 / 800
Pending	Pending	Pending
Pending	Pending	Pending

General Specifications (cont'd)

DC Current Drain (VRX1000 Only):

VRX1000 Off	0.01 A Max
VRX1000 Standby	0.8 A
VRX1000 Receive	0.8 A
VRX1000 Transmit	3.0 A

External Connectors:

Antenna	Mini UHF
Computer Interface	Mini USB
Mobile Radio	DB25
Auxiliary / Options	DB15 (Y cable)
DC Power	M12 Circular

Operating Temperature:

-30°C to + 60°C

Storage Temperature:

-40°C to + 85°C

Protection Against Liquids:

IP54

Antenna Impedance:

50 Ohms

Duty Cycle:

50% Receive / 50% Transmit



Transmitter Specifications

	VHF	UHF	700 / 800
Frequency Band [MHz]	136-174	380-430 450-512	764-776 851-869
Power Output @ Antenna Port	Programmable 0.5 – 3 Watts		
TCT Option	15 sec to 15 min or Disabled		
Max Spurious Output	-20 dBm		
Frequency Stability (-30°C to +60°C; +25°C Ref.)	+/- 0.5ppm		
FM Hum and Noise 12.5 / 25 kHz	34 dB / 40 dB		
Audio Response	+1, -3 dB of 6 dB / octave pre-emphasis characteristic over 300 Hz – 3 kHz		
Audio Distortion	< 2%		

Receiver Specifications

	VHF	UHF	700 / 800
Frequency Band [MHz]	136-174	380-430 450-512	764-776 851-869
Receiver Sensitivity	Analog 12 dB SINAD: -115 dBm Digital P25 5% BER: -115 dBm		
Frequency Stability (-30°C to +60°C; +25°C Ref.)	+/- 0.5ppm		
Selectivity 12.5 / 25 kHz	60 dB / 70 dB		
Intermodulation	70 dB		
Spurious Rejection	70 dB		
Analog Mode Deviation 12.5 / 25 kHz	+/-2.5 kHz / +/-5 kHz		
Frequency Deviation for C4FM (P25)	Low Level: 841 – 1037 Hz High Level: 2543 – 3110 Hz		
Analog Mode FM Hum and Noise 12.5 / 25 kHz	34 dB / 40 dB		
Audio Output (Repeater Detect Audio)	600 mV RMS nominal, flat response		
Audio Response	+1, -3 dB of 6 dB / octave de-emphasis characteristic over 300 Hz – 3 kHz		
Audio Distortion	< 2%		

Military Standards Compliance

MIL-STD-810G

Pending

NOTE: Specifications subject to change without notice.

To Ensure interference-free performance when both the Mobile Radio and the VRX are active, the two antennas must be mounted in such way as to provide 30dB minimum antenna isolation.



VRX1000 shown with APX™ Mobile radio